

Safety Data Sheet according to WHS Regulations

Printing Date: 20.10.2022

Version Number: 1.0

Revision Date: 20.10.2022

# **1 Identification**

## **Product identifier:**

Trade name: Silcor Top Coat 80 (Resin)

Relevant identified uses of the substance or mixture, and uses advised against:

Relevant identified uses of the substance or mixture: Waterproofing.

Identified uses advised against: No further relevant information available.

## Details of the supplier of the safety data sheet:

Manufacturer/supplier:

GCP Australia Pty. Ltd. 14 Colebard Street West Archerfield, Queensland 4108 Australia

### Further information obtainable from:

Tel: 1800 334 444 Fax: +61 7-3275-7801

APMSDS@gcpat.com

Emergency telephone number: After hours - Tel. No. 1800 039 008

# 2 Hazard(s) Identification

### **Classification of the substance or mixture:**

Flam. Liq. 3 H226 Flammable liquid and vapour.

Acute Tox. 5 H313 May be harmful in contact with skin.

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Carc. 2 H351 Suspected of causing cancer. Route of exposure: Inhalation.

STOT SE 3 H335 May cause respiratory irritation.

## Label elements:

GHS label elements The product is classified and labelled according to the Globally Harmonized System (GHS).

### Hazard pictograms



Signal word Warning

**Hazard-determining components of labelling:** Xylene (mixture of isomers) Titanium dioxide

# Hazard statements

Flammable liquid and vapour. May be harmful in contact with skin. Harmful if inhaled. Causes skin irritation. Suspected of causing cancer. Route of exposure: Inhalation. May cause respiratory irritation. **Precautionary statements** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

Version Number: 1.0

Revision Date: 20.10.2022

# Trade name: Silcor Top Coat 80 (Resin)

Keep away from heat/sparks/open flames/hot surfaces. No smoking.	(Contd. of page 1)
Ground/bond container and receiving equipment.	
Use explosion-proof electrical/ventilating/lighting equipment.	
Use only non-sparking tools.	
Take precautionary measures against static discharge.	
Avoid breathing dust/fume/gas/mist/vapours/spray.	
Wash thoroughly after handling.	
Use only outdoors or in a well-ventilated area.	
Wear protective gloves/protective clothing/eye protection/face protection.	
IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.	
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.	
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.	
IF exposed or concerned: Get medical advice/attention.	
If skin irritation occurs: Get medical advice/attention.	
Take off contaminated clothing and wash it before reuse.	
In case of fire: Use CO2, powder or water spray to extinguish.	
Store in a well-ventilated place. Keep container tightly closed.	
Store in a well-ventilated place. Keep cool.	
Store locked up.	
Dispose of contents/container in accordance with local/regional/national/international regulations.	
Hazard description: Flammable	
Other hazards:	
Results of PBT and vPvB assessment:	
<b>PBT:</b> Not applicable.	ľ

**PBT:** Not applicable. **vPvB:** Not applicable.

# **3** Composition and Information on Ingredients

# **Chemical characterization: Mixture:**

Description: Mixture of substances listed below with non-hazardous additions.

Dangerous components:			
1330-20-7	Xylene (mixture of isomers)	30-<50%	
	Flam. Liq. 3, H226 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; STOT SE 3, H335		
13463-67-7	Titanium dioxide	20-<25%	
	Carc. 2, H351		

### Additional information:

Ingredients determined not to be hazardous are present in concentrations that do not exceed the relevant cut-off concentrations as found from NOHSC publication 'List of Designated Hazardous Substances' or have been found NOT to meet the criteria of a hazardous substance as defined in the NOHSC publication 'Approved Criteria for Classifying Hazardous Substances'.

# **4 First Aid Measures**

# Description of first aid measures:

General information: Get medical advice/attention if you feel unwell.

After inhalation:

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

IF INHALED: Call a doctor if you feel unwell.

After skin contact: Wash with plenty of soap and water.

After eye contact: Rinse cautiously with water for several minutes.

After swallowing:

Rinse mouth.

Do NOT induce vomiting.

### Safety Data Sheet according to WHS Regulations

Printing Date: 20.10.2022

Version Number: 1.0

Trade name: Silcor Top Coat 80 (Resin)

(Contd. of page 2)

Revision Date: 20.10.2022

Information for doctor:

Most important symptoms and effects, both acute and delayed: Dizziness

Indication of any immediate medical attention and special treatment needed:

If skin irritation occurs: Get medical advice/attention.

# **5 Fire Fighting Measures**

Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fire with alcohol resistant foam.

For safety reasons unsuitable extinguishing agents: Water jet.

Special hazards arising from the substance or mixture: CO, CO2.

Advice for firefighters:

Protective equipment: Wear self-contained respiratory protective device.

Additional information: Collect contaminated fire fighting water separately. It must not enter the sewage system.

## **6 Accidental Release Measures**

## Personal precautions, protective equipment and emergency procedures:

Ensure adequate ventilation.

Wear protective equipment. Keep unprotected persons away.

Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system.

Methods and material for containment and cleaning up: Send for recovery or disposal in suitable receptacles.

### **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

# 7 Handling and Storage

## HANDLING

## Precautions for safe handling:

Prevent formation of aerosols.

Flammable mixtures with air can be formed in emptied containers. Do not puncture, cut, drill, heat or weld uncleaned drums.

Do not eat, drink or smoke when using this product.

Store in a well-ventilated place. Keep container tightly closed.

Keep only in original container.

Use only outdoors or in a well-ventilated area.

Information about fire - and explosion protection:



Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Use explosion-proof apparatus / fittings and spark-proof tools.

(Contd. on page 4)

(Contd. of page 3)

### Safety Data Sheet according to WHS Regulations

Printing Date: 20.10.2022

Version Number: 1.0

Revision Date: 20.10.2022

# Trade name: Silcor Top Coat 80 (Resin)

Empty containers may retain hazardous residue, both liquid and vapour. Do not cut, drill, grind or weld on or near container, whether empty or full.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Ground/bond container and receiving equipment.

## Conditions for safe storage, including any incompatibilities:

### STORAGE

Information about storage in one common storage facility: Keep respiratory protective device available.

### Further information about storage conditions:

Keep container tightly sealed.

Protect from frost.

Store in a dry place.

**Control parameters:** 

Keep cool.

Specific end use(s): No further relevant information available.

## 8 Exposure controls and personal protection

### Additional information about design of technical facilities: No further data; see item 7.

#### Ingredients with limit values that require monitoring at the workplace: 1330-20-7 Xylene (mixture of isomers) Short-term value: 655 mg/m<sup>3</sup>, 150 ppm WES (Australia) Long-term value: 350 mg/m<sup>3</sup>, 80 ppm Short-term value: 441 mg/m<sup>3</sup>, 100 ppm WEL (Great Britain) Long-term value: 220 mg/m<sup>3</sup>, 50 ppm Sk; BMGV PEL (USA) Long-term value: 435 mg/m<sup>3</sup>, 100 ppm REL (USA) Short-term value: 655 mg/m<sup>3</sup>, 150 ppm Long-term value: 435 mg/m<sup>3</sup>, 100 ppm TLV (USA) Long-term value: 20 ppm BEI, A4 13463-67-7 Titanium dioxide Long-term value: 10 mg/m<sup>3</sup> WES (Australia)

,	8 8
WEL (Great Britain)	Long-term value: 10* 4** mg/m <sup>3</sup>
	*total inhalable **respirable
PEL (USA)	Long-term value: 15* mg/m <sup>3</sup>
	*total dust
REL (USA)	See Pocket Guide App. A
TLV (USA)	Long-term value: 0.2* 2.5** mg/m <sup>3</sup>
	resp. fraction, *nanoscale, **finescale, A3

### Ingredients with biological limit values: 1330-20-7 Xylene (mixture of isomers)

1550-20-7 Ayıcıne (illiz	
BMGV (Great Britain)	650 mmol/mol creatinine
	Medium: urine
	Sampling time: post shift
	Parameter: methyl hippuric acid
BEI (USA)	1.5 g/g creatinine
	Medium: urine
	Time: end of shift
	Parameter: Methylhippuric acids

Additional information: Based on the lists valid at the date of SDS creation.

(Contd. on page 5)

Version Number: 1.0

Trade name: Silcor Top Coat 80 (Resin)

Exposure controls:

## PERSONAL PROTECTIVE EQUIPMENT

### General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

### **Respiratory protection:**

Control exposure to ingredients with workplace control parameters if mentioned above. If no ingredients are listed, respiratory protection is generally not required.

If exposure limits are listed and may be exceeded, use approved respiratory protective equipment and filter type appropriate for the listed ingredients. (NIOSH, CEN, etc.).

Protection of hands: Protective gloves.

Material of gloves: Rubber gloves.

Penetration time of glove material:

The exact breakthrough time has to be determined by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Safety glasses with side shield protection.

### **Body protection:**

Use personal protective equipment as required.

Take off contaminated clothing and wash before reuse.

9 Physical and Chemical Properties			
Information on basic physical	Information on basic physical and chemical properties:		
GENERAL INFORMATION			
Appearance:			
Form:	Liquid.		
Colour:	Coloured		
Odour:	Slight Musty		
Odour threshold:	Not determined.		
pH-value (~):	Not determined.		
Change in conditions:- Melting point/freezing point: Initial boiling point and boiling ran Flash point:	Undetermined. nge: >138 °C 30 °C		
Flammability (solid, gas):	Flammable.		
Ignition temperature:	Not determined.		
Decomposition temperature:	Not determined.		
Auto-ignition temperature:	Not determined.		
Explosive properties:	In use, may form flammable/explosive vapour-air mixture.		
EXPLOSION LIMITS			
Lower:	Not determined.		
Upper:	Not determined.		
Vapour pressure:	Not determined.		
Density at 20 °C:	$1.1 \text{ g/cm}^3$		
Vapour density:	Not determined.		
Evaporation rate:	Not determined.		
Solubility in/Miscibility with:- Water:	Not miscible or difficult to mix.		
		(Contd. on page	

Revision Date: 20.10.2022

(Contd. of page 4)

## Safety Data Sheet according to WHS Regulations

Printing Date: 20.10.2022

Version Number: 1.0

Trade name: Silcor Top Coat 80 (Resin)

	(Contd. of page 5)
Partition coefficient: n-octanol/water:	Not determined.
VISCOSITY	
Dynamic:	Not determined.
Kinematic:	Not determined.
Molecular weight	Not determined.
Other information:	No further relevant information available.

# **10 Stability and Reactivity**

**Reactivity:** 

Stable under normal conditions. No further relevant information available.

## Chemical stability:

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

**Possibility of hazardous reactions** No dangerous reactions known.

No further relevant information available.

Conditions to avoid: Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Incompatible materials: No further relevant information available.

Hazardous decomposition products: Carbon monoxide and carbon dioxide

# **11 Toxicological Information**

### Information on toxicological effects:

### ACUTE TOXICITY

LD/LC50 values relevant for classification:

1330-20-7 Xylene (mixture of isomers)

Oral LD50 3,523 mg/kg (rat)

Inhalative | LC50, 4h | 26 mg/m<sup>3</sup> (rat) **13463-67-7 Titanium dioxide** 

Oral LD50 >5,000 mg/kg (rat)

### Primary irritant effect

# Skin corrosion/irritation

Causes skin irritation. May be harmful in contact with skin.

Serious eye damage/irritation No irritating effect.

**Inhalation:** Harmful if inhaled. May cause respiratory irritation.

Additional toxicological information: Suspected of causing cancer. Route of exposure: Inhalation.

GHS Health Hazards : Carcinogenicity: Category 2 - Suspected of causing cancer. Other information : The product was classified according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version.

(Contd. on page 7)

AU

Version Number: 1.0

Trade name: Silcor Top Coat 80 (Resin)

**12 Ecological Information** 

## **Toxicity:**

AQUATIC TOXICITY No further relevant information available.

Persistence and degradability: No further relevant information available.

# **BEHAVIOUR IN ENVIRONMENTAL SYSTEMS**

Bioaccumulative potential: No further relevant information available.

Mobility in soil: No further relevant information available.

# ADDITIONAL ECOLOGICAL INFORMATION

General notes: Not known to be hazardous to water.

## **Results of PBT and vPvB assessment:**

**PBT:** Not applicable. **vPvB:** Not applicable.

Other adverse effects: No further relevant information available.

# **13 Disposal considerations**

## Waste treatment methods:

**Recommendation:** 



Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Refer to State Land Waste Authority for disposal considerations.

## **UNCLEANED PACKAGING**

Recommendation: Disposal must be made according to official regulations.

l4 Transport information		
UN-Number ADG, IMDG, IATA	UN1139	
UN proper shipping name ADG, IMDG, IATA	COATING SOLUTION	
Transport hazard class(es) ADG, IMDG, IATA		
Class Label	3 Flammable liquids. 3	
Packing group ADG, IMDG, IATA	III	
Environmental hazards:	Not applicable.	
Special precautions for user: Hazard identification number (Kemler code): EMS Number:	Warning: Flammable liquids. 30 F-E, <u>S-E</u>	
		(Contd. on page 8)

(Contd. of page 6)

Version Number: 1.0

Revision Date: 20.10.2022

# Trade name: Silcor Top Coat 80 (Resin)

		(Contd. of page 7)	
Stowage Category	А		
Transport in bulk according to Annex I	Transport in bulk according to Annex II of		
MARPOL73/78 and the IBC Code:	Not Regulated		
Transport/Additional information:			
ADG Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml 3 D/E		
IMDG Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml		

## **15 Regulatory information**

Safety, health and environmental regulations/legislation specific for the substance or mixture:

See Section 2 for hazard identification.

None of the ingredients is listed.

Australia: Priority Existing Chemicals

National regulations:

Other regulations, limitations and prohibitive regulations: All ingredients are listed on AICS.

Registered in the international inventory lists: AICS (Australia)

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

# **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

### **Relevant phrases:**

H226 Flammable liquid and vapour.

- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation. H351 Suspected of causing cancer.
- H351 Suspected of causing cancer

## **Department issuing SDS:**

Product Stewardship Department GCP Applied Technologies (UK) Limited 487/488 Ipswich Road, Slough, Berkshire SL1 4EP

Tel: +44 (0)1753 490 000

**Contact:** 

The first date of preparation: 19.10.2022

Number of revision times and the latest revision date:  $1.0\,/\,20.10.2022$ 

Sources: Raw material suppliers' safety data sheets were used as key data sources in the preparation of this safety data sheet.