

Safety Data Sheet according to WHS Regulations

Printing Date: 15.09.2022

Version Number: 1.0

Revision Date: 15.09.2022

1 Identification

Product identifier:Trade name: SILCOR 560 HB**Relevant identified uses of the substance or mixture, and uses advised against:**

Relevant identified uses of the substance or mixture: Waterproofing.

Identified uses advised against: No further relevant information available.

Details of the supplier of the safety data sheet:**Manufacturer/supplier:**

GCP Australia Pty. Ltd.
14 Colebard Street West
Archerfield, Queensland 4108
Australia

Further information obtainable from:

Tel: 1800 334 444
Fax: +61 7-3275-7801
APMSDS@gcpat.com

Emergency telephone number: After hours - Tel. No. 1800 039 008

2 Hazard(s) Identification

Classification of the substance or mixture:

Flam. Liq. 4 H227 Combustible liquid.

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Label elements:**GHS label elements** The product is classified and labelled according to the Globally Harmonized System (GHS).**Hazard pictograms**

GHS05 GHS07 GHS08

Signal word Danger**Hazard-determining components of labelling:**

Xylene (mixture of isomers)

poly[oxy(methyl-1,2-ethanediy)]-alpha-(2-aminomethylethyl)-omega-(2-aminomethylethoxy)- reaction product with benzaldehyde

4-isocyanatosulphonyltoluene

Hazard statements

Combustible liquid.

Harmful if inhaled.

Causes skin irritation.

Causes serious eye damage.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Precautionary statements

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Safety Data Sheet

according to WHS Regulations

Printing Date: 15.09.2022

Version Number: 1.0

Revision Date: 15.09.2022

Trade name: SILCOR 560 HB

(Contd. of page 1)

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

[In case of inadequate ventilation] wear respiratory protection.

IF ON SKIN: Wash with plenty of water.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor.

If skin irritation occurs: Get medical advice/attention.

If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

Take off contaminated clothing and wash it before reuse.

In case of fire: Use CO₂, powder or water spray to extinguish.

Store in a well-ventilated place.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Information concerning particular hazards for human and environment:

Description of Classification: Classified as hazardous according to the criteria of Safe Work Australia.

Other hazards:

Results of PBT and vPvB assessment:

PBT: Not applicable.

vPvB: Not applicable.

3 Composition and Information on Ingredients

Chemical characterization: Mixture:

Description: Mixture of substances listed below with non-hazardous additions.

Dangerous components:

28553-12-0	Diisononyl phthalate	10-<20%
1330-20-7	Xylene (mixture of isomers)	5-<10%
	Flam. Liq. 3, H226 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; STOT SE 3, H335	
524730-13-0	poly[oxy(methyl-1,2-ethanediyl)]-alpha-(2-aminomethylethyl)-omega-(2-aminomethylethoxy)-reaction product with benzaldehyde	3-<5%
	Skin Corr. 1B, H314; Eye Dam. 1, H318	
4083-64-1	4-isocyanatosulphonyltoluene	1-<3%
	Resp. Sens. 1, H334 Skin Irrit. 2, H315; Eye Irritation 2A, H319; STOT SE 3, H335	
6425-39-4	2,2'-Dimorpholinyl-diethyl ether	1-<3%
	Skin Irrit. 2, H315; Eye Irritation 2A, H319	
13463-67-7	Titanium dioxide	1-<3%

Additional information:

Ingredients determined not to be hazardous are present in concentrations that do not exceed the relevant cut-off concentrations as found from NOHSC publication 'List of Designated Hazardous Substances' or have been found NOT to meet the criteria of a hazardous substance as defined in the NOHSC publication 'Approved Criteria for Classifying Hazardous Substances'.

4 First Aid Measures

Description of first aid measures:

General information: Get medical advice/attention if you feel unwell.

After inhalation:

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

IF INHALED: Call a doctor if you feel unwell.

After skin contact: Wash with plenty of soap and water.

After eye contact: Rinse cautiously with water for several minutes.

(Contd. on page 3)

AU

Safety Data Sheet
according to WHS Regulations

Printing Date: 15.09.2022

Version Number: 1.0

Revision Date: 15.09.2022

Trade name: *SILCOR 560 HB*

(Contd. of page 2)

After swallowing:

Rinse mouth.

Do NOT induce vomiting.

Information for doctor:**Most important symptoms and effects, both acute and delayed:** Dizziness**Indication of any immediate medical attention and special treatment needed:**

If skin irritation occurs: Get medical advice/attention.

5 Fire Fighting Measures

Suitable extinguishing agents:CO₂, extinguishing powder or water spray. Fight larger fire with alcohol resistant foam.**For safety reasons unsuitable extinguishing agents:** Water jet.**Special hazards arising from the substance or mixture:** CO, CO₂.**Advice for firefighters:****Protective equipment:** Wear self-contained respiratory protective device.**Additional information:** Collect contaminated fire fighting water separately. It must not enter the sewage system.

6 Accidental Release Measures

Personal precautions, protective equipment and emergency procedures:

Ensure adequate ventilation.

Wear protective equipment. Keep unprotected persons away.

Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system.**Methods and material for containment and cleaning up:**

Use neutralising agent.

Send for recovery or disposal in suitable receptacles.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and Storage

HANDLING**Precautions for safe handling:**

Prevent formation of aerosols.

Do not eat, drink or smoke when using this product.

Store in a well-ventilated place. Keep container tightly closed.

Keep only in original container.

Use only outdoors or in a well-ventilated area.

Information about fire - and explosion protection:

Empty containers may retain hazardous residue, both liquid and vapour. Do not cut, drill, grind or weld on or near container, whether empty or full.

(Contd. on page 4)

AU

Safety Data Sheet
according to WHS Regulations

Printing Date: 15.09.2022

Version Number: 1.0

Revision Date: 15.09.2022

Trade name: SILCOR 560 HB

(Contd. of page 3)

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Conditions for safe storage, including any incompatibilities:

STORAGE

Information about storage in one common storage facility: No special measures required.

Further information about storage conditions:

Keep container tightly sealed.

Protect from frost.

Store in a dry place.

Keep cool.

Specific end use(s): No further relevant information available.

8 Exposure controls and personal protection

Additional information about design of technical facilities: No further data; see item 7.

Control parameters:

Ingredients with limit values that require monitoring at the workplace:

28553-12-0 Diisononyl phthalate

WEL (Great Britain) Long-term value: 5 mg/m³

1330-20-7 Xylene (mixture of isomers)

WES (Australia) Short-term value: 655 mg/m³, 150 ppm
Long-term value: 350 mg/m³, 80 ppm

WEL (Great Britain) Short-term value: 441 mg/m³, 100 ppm
Long-term value: 220 mg/m³, 50 ppm
Sk; BMGV

PEL (USA) Long-term value: 435 mg/m³, 100 ppm

REL (USA) Short-term value: 655 mg/m³, 150 ppm
Long-term value: 435 mg/m³, 100 ppm

TLV (USA) Long-term value: 20 ppm
BEI, A4

4083-64-1 4-isocyanatosulphonyltoluene

WES (Australia) Short-term value: 0.07 mg/m³
Long-term value: 0.02 mg/m³
Sen, as -NCO

WEL (Great Britain) Short-term value: 0.07 mg/m³
Long-term value: 0.02 mg/m³
Sen; as -NCO

13463-67-7 Titanium dioxide

WES (Australia) Long-term value: 10 mg/m³

WEL (Great Britain) Long-term value: 10* 4** mg/m³
*total inhalable **respirable

PEL (USA) Long-term value: 15* mg/m³
*total dust

REL (USA) See Pocket Guide App. A

TLV (USA) Long-term value: 0.2* 2.5** mg/m³
resp. fraction, *nanoscale, **finescale, A3

(Contd. on page 5)

AU

Safety Data Sheet according to WHS Regulations

Printing Date: 15.09.2022

Version Number: 1.0

Revision Date: 15.09.2022

Trade name: SILCOR 560 HB

(Contd. of page 4)

Ingredients with biological limit values:
1330-20-7 Xylene (mixture of isomers)

BMGV (Great Britain)	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid
BEI (USA)	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids

Additional information: Based on the lists valid at the date of SDS creation.

Exposure controls:
PERSONAL PROTECTIVE EQUIPMENT
General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Respiratory protection:

Control exposure to ingredients with workplace control parameters if mentioned above. If no ingredients are listed, respiratory protection is generally not required.

If exposure limits are listed and may be exceeded, use approved respiratory protective equipment and filter type appropriate for the listed ingredients. (NIOSH, CEN, etc.).

Protection of hands: Protective gloves.

Material of gloves:

Rubber gloves.

Nitrile rubber.

Penetration time of glove material:

The exact breakthrough time has to be determined by the manufacturer of the protective gloves and has to be observed.

Eye protection:


Safety glasses with side shield protection.

Body protection:

Use personal protective equipment as required.

Take off contaminated clothing and wash before reuse.

9 Physical and Chemical Properties

Information on basic physical and chemical properties:
GENERAL INFORMATION
Appearance:

Form:	Liquid.
Colour:	Grey.
Odour:	Slight Musty
Odour threshold:	Not determined.

pH-value (~): Not determined.

Change in conditions:-

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	>138 °C
Flash point:	>72 °C

(Contd. on page 6)

AU

Safety Data Sheet according to WHS Regulations

Printing Date: 15.09.2022

Version Number: 1.0

Revision Date: 15.09.2022

Trade name: SILCOR 560 HB

(Contd. of page 5)

Flammability (solid, gas):	Not applicable.
Ignition temperature:	Not determined.
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Not determined.
Explosive properties:	Not determined.
EXPLOSION LIMITS	
Lower:	Not determined.
Upper:	Not determined.
Vapour pressure:	Not determined.
Density at 20 °C:	1.5 g/cm ³
Vapour density:	Not determined.
Evaporation rate:	Not determined.
Solubility in/Miscibility with:-	
Water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
VISCOSITY	
Dynamic:	Not determined.
Kinematic:	Not determined.
Molecular weight	Not determined.
Other information:	No further relevant information available.

10 Stability and Reactivity

Reactivity:

Stable under normal conditions.

No further relevant information available.

Chemical stability:
Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

Possibility of hazardous reactions

No dangerous reactions known.

No further relevant information available.

Conditions to avoid: No further relevant information available.

Incompatible materials: No further relevant information available.

Hazardous decomposition products: Carbon monoxide and carbon dioxide

11 Toxicological Information

Information on toxicological effects:
ACUTE TOXICITY
LD/LC50 values relevant for classification:
1330-20-7 Xylene (mixture of isomers)

Oral	LD50	3,523 mg/kg (rat)
------	------	-------------------

Inhalative	LC50, 4h	26 mg/m ³ (rat)
------------	----------	----------------------------

13463-67-7 Titanium dioxide

Oral	LD50	>5,000 mg/kg (rat)
------	------	--------------------

Primary irritant effect
Skin corrosion/irritation Causes skin irritation.

Serious eye damage/irritation Causes serious eye damage.

Inhalation:

Harmful if inhaled.

(Contd. on page 7)

AU

Safety Data Sheet
according to WHS Regulations

Printing Date: 15.09.2022

Version Number: 1.0

Revision Date: 15.09.2022

Trade name: *SILCOR 560 HB*

(Contd. of page 6)

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Respiratory or skin sensitisation May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Other information :

The product was classified according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version.

12 Ecological Information

Toxicity:

AQUATIC TOXICITY No further relevant information available.

Persistence and degradability: No further relevant information available.

BEHAVIOUR IN ENVIRONMENTAL SYSTEMS

Bioaccumulative potential: No further relevant information available.

Mobility in soil: No further relevant information available.

ADDITIONAL ECOLOGICAL INFORMATION

General notes: Must not reach sewage water or drainage ditch undiluted or unneutralised.

Results of PBT and vPvB assessment:

PBT: Not applicable.

vPvB: Not applicable.

Other adverse effects: No further relevant information available.

13 Disposal considerations

Waste treatment methods:**Recommendation:**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Refer to State Land Waste Authority for disposal considerations.

UNCLEANED PACKAGING

Recommendation: Disposal must be made according to official regulations.

14 Transport information

UN-Number

ADG, IMDG, IATA

Not Regulated

UN proper shipping name

ADG, IMDG, IATA

Not Regulated

Transport hazard class(es)

ADG, ADN, IMDG, IATA

Class

Not Regulated

Packing group

ADG, IMDG, IATA

Not Regulated

Environmental hazards:

Not applicable.

Special precautions for user:

Not applicable.

(Contd. on page 8)

AU

Safety Data Sheet
according to WHS Regulations

Printing Date: 15.09.2022

Version Number: 1.0

Revision Date: 15.09.2022

Trade name: *SILCOR 560 HB*

(Contd. of page 7)

**Transport in bulk according to Annex II of
MARPOL73/78 and the IBC Code:** Not Regulated

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture:

See Section 2 for hazard identification.

Australia: Priority Existing Chemicals

28553-12-0	Diisononyl phthalate
------------	----------------------

National regulations:

Other regulations, limitations and prohibitive regulations: All ingredients are listed on AICS.

Registered in the international inventory lists: AICS (Australia)

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases:

H226 Flammable liquid and vapour.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

Department issuing SDS:

EHS Department,

Asia Pacific Region

SCIP, Canlubang, Calamba City, Laguna

Philippines 4028

Tel: +63 (02) 8236-6820 to 24

Contact:

The first date of preparation: 28.02.2022

Number of revision times and the latest revision date: 1.0 / 15.09.2022